

### PUMP SPECIFICATIONS

Flow (Max)	350 l/s
Head (Max)	140m
Nominal Duty	300 l/s @ 100 mtrs
Pump Model	RA-P-250x200-464
Pump Speed	1900-2000 rpm
Pump Inlet/outlet	250mm (10") x 200mm (8")
Pipework Size	250mm (10") x 200mm (8")
Solids Handling	Clear Liquid

### RECOMMENDED ENGINES

Make	Model
CAT	C18 ACERT
Volvo Penta	TAD1345VE
Perkins	2806D-E18TA

### SKID SPECS AND DIMENSIONS\*

Skid Base Model	<b>MH2000 (Mining Series)</b>
Fuel Tank Capacity	2000 Litres
Overall Dimensions (mm)	L5500 x W1920 x H3050

### MINING PACKAGE INCLUSIONS


- Heavy duty baffled fuel tank skid base
- 2-Post Lifting frame & roof
- Shun/Bull bar and skid wear plates
- Suction and discharge pipework
- Auto self-priming System (Vacuum Diaphragm)
- Engine control & protection system
- External emergency stop button
- Lockable fuel cap
- Check valve & isolation valve (discharge piping)
- Lockable steel battery enclosure
- Fire extinguisher
- Amber strobe light

### OPTIONAL EXTRAS




- Remote start / stop
- Telemetry systems
- Battery isolator
- Additional external emergency stops (both sides)
- Solar panel and trickle charger
- LED work lights / flashing lights
- Wiggins style quick fill system
- Flowmeter

### OTHER CONFIGURATIONS

- Trailer mounted (open)
- Trailer mounted canopy
- Sound attenuated (Acoustic Canopy)
- Pontoon mounted
- Custom design options available



## BUILT TO BE TOUGH



\*\* Pumpset & pipework drawing shown above are for indicative purpose only. Contact Remko for dimensional as-built drawings & dimensions.

\* Guide only. Technical specifications may vary with the pumpset configuration and details subject to change without notice.